



Material Safety Data Sheet

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER:

Product Name: **Fortron BRAKE SERVICE KIT**

Other Names: **BRAKE SERVICE KIT
BRAKEKIT – Service Kit
1 x FBF500 – Brake & Clutch Fluid 500ml container
1 x FBC200 – Brake & Parts Cleaner 200ml aerosol can**

Recommended Use: This service kit contains two products that will supply the following benefits:

Brake & Clutch Fluid - A special low moisture absorption, high boil point brake fluid, suitable for all cars, trucks and buses under extreme and heavy duty application.

Brake & Parts Cleaner - Brake & Parts Cleaner can be applied without disassembly of brakes. This product removes brake fluid, oil and other contaminants. Can be used for all parts spot cleaning where it is not desirable to wash with water. A build up of brake fluid, oil and other contaminants will detract from the efficiency of the brakes quickly. Brake & Parts Cleaner is specially formulated for the removal of most contaminants and will also stop disc brake 'squeal'. This product will remove brake fluid, oil and other contaminants from: -Chains, Slides, Open Gears, Hinges, Brake Drums, Brake Linings, Brake Pads, Brake Cylinders and Brake Springs.

Supplier: Fortron Automotive Treatments Pty Ltd
14-18 Sangiorgio Court, Osborne Park
Perth, Western Australia 6017
ACN 008 872 197 ABN 12 008 872 197
Phone: (618) 9202 5300 (Monday – Friday 8.00am – 5.00pm)
Fax: (618) 9202 5394
www.fortron.com.au

Emergency Telephone No: 0433 088 498



2. HAZARDS IDENTIFICATION:

CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA OF THE NATIONAL OCCUPATIONAL HEALTH AND SAFETY COMMISSION (NOHSC) AND ALSO WORKSAFE AUSTRALIA

Brake & Clutch Fluid – 500ml bottle

This material is not considered to be hazardous, but should be handled in accordance with good industrial hygiene and safety practices.

Hazard Symbol: This material is not considered to be hazardous

Risk Phrase:

Safety Phrase:

Brake & Parts Cleaner – 200ml aerosol can

Hazard Symbol: Xn Harmful

Risk Phrase: R11 Highly flammable
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R36 Irritating to eyes
R66 Repeated exposure may cause skin dryness or cracking
R67 Vapours may cause drowsiness and dizziness

Safety Phrase: S2 Keep out of the reach of children
S9 Keep container in a well ventilated place
S16 Keep away from sources of ignition – No Smoking
S24/25 Avoid contact with skin and eyes
S29 Do not empty into drains
S51 Use only in well-ventilated areas

3. COMPOSITION/INFORMATION ON INGREDIENTS:

Brake & Clutch Fluid – 500ml bottle

| <u>Chemical Name</u> | <u>CAS Number</u> | <u>Proportion % w/w</u> |
|---------------------------|-------------------|-------------------------|
| Non Hazardous ingredients | No data | 100% |

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

Brake & Parts Cleaner – 200ml aerosol can

| <u>Chemical Name</u> | <u>CAS Number</u> | <u>Proportion % w/w</u> |
|----------------------|-------------------|-------------------------|
| White Spirit | 8052-41-3 | < 15.0% |
| Acetone | 67-64-1 | 10-20% |
| Hexane | 110-54-3 | 20-30% |
| Carbon Dioxide | 124-38-9 | 30-60% |



4. FIRST AID MEASURES:

Brake & Clutch Fluid – 500ml bottle

- Swallowed: If swallowed, **do NOT** induce vomiting. Wash mouth with water and give a glass of water to drink.
- For advice, contact a Poisons Information Centre. Phone Australia 13 1126; New Zealand 03 4747 000 (Not after May 2005) or 0800 764 766; or a doctor (at once).
- Eye: If contact with the eye(s) occur, immediately hold the eye open and wash continuously for at least 15 minutes with fresh running water. Seek medical attention if any pain or redness develops or persists.
- Skin: If product gets on skin, thoroughly wash contacted areas. No further measures should normally be required unless irritation is noticed. If irritation persists, seek medical attention.
- Inhaled: No first aid measures normally required. However, if vapours or mists have been inhaled, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.
- First Aid Facilities: Safety shower, mild soap and eye wash facilities.
- Advice to Doctor: Treat symptomatically. Note the nature of this product.

Brake & Parts Cleaner – 200ml aerosol can

- Swallowed: If swallowed **DO NOT** induce vomiting. Rinse or wash out mouth with plenty of water after which if victim is conscious, give a glass of water to drink. Avoid giving milk or oils, and avoid giving alcohol. Seek medical attention.
- For advice, contact a Poisons Information Centre. Phone Australia 13 1126; New Zealand 03 4747 000 (Not after May 2005) or 0800 764 766; or a doctor (at once).
- Eye: If contact with the eye(s) occur, immediately hold the eye open and wash continuously for at least 15 minutes with fresh running water. Ensure irrigation under eyelids by occasionally lifting the upper and lower lids. Transport to hospital or doctor without delay. Skilled personnel should only undertake removal of contact lenses after an eye injury.
- Skin: If solids or aerosol mists are deposited upon the skin wash affected areas thoroughly with water and soap if available. Remove any adhering solids with industrial skin cleansing cream. Do not use solvents. Seek medical attention in the event of irritation.
- Inhaled: Remove the source of contamination or move the victim to fresh air. Administer artificial respiration if breathing has stopped. Keep at rest. Call for prompt medical attention.
- First Aid Facilities: Safety shower, mild soap and eye wash facilities.



4. FIRST AID MEASURES: - continued

Advice to Doctor: For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:-

1. Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
2. Patients should be quickly evaluated for signs of respiratory distress and give oxygen. Patients with inadequate tidal volumes or poor arterial blood gases should be intubated.
(Ellenhorn and Barceloux : Medical Toxicology)

5. FIRE FIGHTING MEASURES:

Brake & Clutch Fluid – 500ml bottle

This product is classified as a C1 combustible product. There is no risk of an explosion from this product under normal circumstances if it is involved in a fire.

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam, water fog.

Unusual Fire & Explosion Hazards: Fire decomposition products from this product may form toxic mixtures in confined spaces. Violent steam generation or eruption may occur upon application of direct water stream on hot liquid.

Fire Fighting Precautions: When fighting fires involving significant quantities of this product, wear safety boots, non-flammable overalls, gloves, hat, goggles and self contained breathing apparatus. All skin areas should be covered.

Hazchem Code: Not applicable

Brake & Parts Cleaner – 200ml aerosol can

Extinguishing Media: In case of fire use water spray, dry chemical or CO².

Unusual Fire & Explosion Hazards: Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Severe explosion hazard, in the form of vapour, when exposed to flame or spark. Vapour may travel considerable distance to source of ignition. Heating may cause expansion or decomposition leading to violent rupture of containers. Containers may explode on exposure to naked flames. Rupturing containers may rocket and scatter burning materials. Hazards may not be restricted to pressure effects. May emit acrid, poisonous or corrosive fumes. On combustion, may emit toxic fumes of carbon monoxide (CO). Other combustion products include carbon dioxide. (CO²).

Fire Fighting Precautions: Fire fighters should wear full protective clothing and self-contained breathing apparatus. If large amounts, or corrosive or toxic products are involved, wear SCBA and chemical splash suit.

Fight fire from protected position or use unmanned hose holders or monitor nozzles. If safe to do so, move undamaged containers from fire area. Do not approach hot containers. Cool containers with water before handling. If impossible to extinguish fire, protect surroundings, withdraw from area and allow fire to burn.

Hazchem Code: 2Y



6. ACCIDENTAL RELEASE MEASURES:

Brake & Clutch Fluid – 500ml bottle

Emergency Procedures: Stop leak if safe to do so, and contain spill.

Methods and Materials for Containment and Clean Up:- Small Spills: Minor spill do not normally need any special cleanup measures.

Large Spills: In the event of a major spill, prevent spillage from entering drains or water courses. As a minimum, wear overalls, goggles and gloves. Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. Avoid using sawdust or other combustible material. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Can be slippery, especially when wet. Recycle containers wherever possible. After spills, wash area preventing runoff from entering drains, if a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Dispose of only in accord with all regulations.

Brake & Parts Cleaner – 200ml aerosol can

Emergency Procedures: Methods and materials for containment and clean up:-

Procedures in Case of Breakage or Leakage:-

Minor Spill:
Clean up spills immediately. Avoid breathing vapours and contact with skin and eyes. Wear protective clothing, impervious gloves and safety glasses. Shut off all possible sources of ignition and increase ventilation. Wipe up. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely.

Major Spill:
Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage entering drains or watercourses. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Water spray or fog may be used to disperse/absorb vapour. Absorb or cover spill with sand, earth, inert materials or vermiculite. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Collect residues and seal in labelled drums for disposal.

Other Information: Consult State Land Waste Management Authority for disposal. Discharge contents of damaged aerosol cans at approved site. Allow small quantities to evaporate. DO NOT incinerate or puncture aerosol cans. Bury residues and empty aerosol cans at approved site.



7. HANDLING AND STORAGE:

Brake & Clutch Fluid – 500ml bottle

Precautions for Safe Handling: Avoid contact with skin and eyes.

Respiratory Protection: Where vapours, mists or spray is generated and exposure standards are exceeded, select and use respirators in accordance with AS/NZS1715/1716. The use of an approved respirator with organic vapour and dust/mist filters. Filter capacity and respirator type depends on exposure levels for each individual circumstance.

Skin Protection:

Protective Gloves : Impermeable protective gloves should be worn when you are using this product, to prevent irritation. For help in selecting suitable equipment, consult AS2161.

Clothing : This product is essentially safe to use without special protective clothing. However, its use is recommended as a good industrial practice. Consult AS2919 for advice on Industrial Clothing.

Safety Boots : Wear safety boots in industrial situations is advisory. Consult AS/NZS2210 for advice on Occupational Protective Footwear.

Eye Protection: Protective eyewear is not normally necessary when using this product. However, it is always prudent to use protective eyewear. Consult AS1336 and AS/NZS1337 for advice on Industrial Eye Protection.

Hygiene Recommendations: Always wash hands before smoking, eating or using the toilet. Wash contaminated clothing and other protective equipment before storing and re-using.

Conditions for Safe Storage: No special storage requirements. Containers should be kept closed in order to minimise contamination. Keep from extreme heat and open flames, and make sure that the product does not come into contact with substances listed under "Materials to Avoid" below.

This product is combustible and therefore, for Storage, meets the definition of Dangerous Goods in some states. We suggest you consult your state's Dangerous Goods law in order to clarify your obligations regarding the storage of this product.

Brake & Parts Cleaner – 200ml aerosol can

Precautions for Safe Handling: Store in original containers. Check that containers are clearly labelled.

Conditions for Safe Storage: Store in original containers in approved flameproof area. Do not store in pits, depressions, basements or areas where vapour may be trapped. No smoking, naked lights, heat or ignition sources.



7. HANDLING AND STORAGE: - continued

Keep containers securely sealed. Contents under pressure.

Avoid storage with oxidising agents, strong acids and alkalis, organic peroxides, alkali metals, aluminium and magnesium powders.

Store away from incompatible materials. Store in a cool, dry well ventilated area. Avoid storage at temperatures higher than 40°C. Store in an upright position. Protect containers against physical damage.

Check regularly for spills and leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION:

Brake & Clutch Fluid – 500ml bottle

A time weighted average (TWA) concentration for an 8 hour day, and 5 day week has not been established by NOHSC Australia for any of the major ingredients in this product. There is a blanket limit of 10mg/m³ for dusts or mists when limits have not otherwise been established.

Brake & Parts Cleaner – 200ml aerosol can

None assigned for mixture. Refer to individual constituents.

Exposure Standard means the average concentration of a particular substance in the worker's breathing zone, exposure to which, according to current knowledge, should not cause adverse health effects nor cause undue discomfort to nearly all workers. It can be of three forms; time-weighted average (TWA), peak limitation, or short term exposure limit (STEL).

Time-weighted average (TWA) is defined as the concentration of that substance over an eight-hour working shift, and apply to an eight-hour day, for a five-day working week over an entire working lifetime. Short Term Exposure Limits (STEL) and Peak Limitations may also be specified for short periods of exposure such as 15 minutes.

Brake & Clutch Fluid – 500ml bottle

Engineering Controls:

In industrial situations, concentration value below the TWA value should be maintained. Values may be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify the process of environment to reduce the problem.

Personal Protective Equipment:

Avoid, as far as reasonably practicable, inhalation of vapour, mists or fumes generated during use.



8. EXPOSURE CONTROLS/PERSONAL PROTECTION: - continued

Brake & Clutch Fluid – 500ml bottle

Respiratory Protection: Where vapours, mists or spray is generated and exposure standards are exceeded, select and use respirators in accordance with AS/NZS1715/1716. The use of an approved respirator with organic vapour and dust/mist filters. Filter capacity and respirator type depends on exposure levels for each individual circumstance.

Skin Protection:

Protective Gloves : Impermeable protective gloves should be worn when you are using this product, to prevent irritation. For help in selecting suitable equipment, consult AS2161.

Clothing : This product is essentially safe to use without special protective clothing. However, its use is recommended as a good industrial practice. Consult AS2919 for advice on Industrial Clothing.

Safety Boots : Wear safety boots in industrial situations is advisory. Consult AS/NZS2210 for advice on Occupational Protective Footwear.

Eye Protection: Protective eyewear is not normally necessary when using this product. However, it is always prudent to use protective eyewear. Consult AS1336 and AS/NZS1337 for advice on Industrial Eye Protection.

Hygiene Recommendations: Always wash hands before smoking, eating or using the toilet. Wash contaminated clothing and other protective equipment

Engineering Controls: Use adequate ventilation to keep the airborne concentrations of this material below the WORKSAFE exposure standards for mineral oils mists. Local exhaust ventilation and/or enclosure of the process are preferred in these cases.

Brake & Parts Cleaner – 200ml aerosol cans

Engineering Controls: Use adequate ventilation to keep the airborne concentrations below the Worksafe exposure standards. If inhalation risk of overexposure exists, wear AS1715/1716 approved respirator – air-purifying type. Correct fit is essential to obtain adequate protection.

Provide adequate ventilation in warehouse or closed storage areas.

Personal Protective Equipment:

Respirator Type (AS1716)

Airborne concentrations should be kept to lowest levels possible. If vapour, mist or dust is generated and the occupational limit of the product or any component of the product, is exceeded, use appropriate AS/NZS1715/1716 approved air purifying or air supplied respirator after determining the airborne concentration of the contaminant. Air supplied respirators should be worn when airborne concentration of the contaminant or oxygen content is unknown.



8. EXPOSURE CONTROLS/PERSONAL PROTECTION: - continued

Brake & Parts Cleaner – 200ml aerosol can

Skin Protection:

No special equipment needed when handling small quantities. Soiled work clothing should be laundered or dry-cleaned.

Eye Protection

No special eye protection is necessary when handling in small quantities. If eye contact is likely, then it is recommended that safety glasses or goggles be used. Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.

Hygiene Recommendations: Keep an eye wash fountain available. Keep safety shower available. If clothing is contaminated, remove clothing and thoroughly wash the affected area. Launder contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Brake & Clutch Fluid – 500ml bottle

| | |
|----------------------------|--|
| Appearance: | Colourless to amber liquid (when not dyed) |
| Odour: | No odour |
| pH: | |
| Vapour Pressure: | Less than 1 kPa @ 20°C |
| Vapour Density: | |
| Boiling Point: | Above 270°C @ 100kPa |
| Melting Point: | Below -50°C |
| Solubility in Water: | Completely soluble |
| Specific Gravity: | |
| Flashpoint: | Above 120°C (PMCC) |
| Flammability Limits: | LEL UEL |
| Auto Ignition Temperature: | 310°C |
| Viscosity: | 1300cSt @ -40°C, 2.0cST @ 100°C |
| Corrosiveness: | Not corrosive |
| Volatile material: | Not specific data. Expected to be low at 100°C |

Brake & Parts Cleaner – 200ml aerosol can

| | |
|----------------------------|--|
| Appearance: | Rapidly evaporating, colourless liquid |
| Odour: | Solvent odour |
| pH: | Not available |
| Vapour Pressure: | 300-2400 (propellant) |
| Vapour Density: | > 1 (air=1) |
| Boiling Point: | -40°C (propellant) |
| Melting Point: | Not applicable |
| Solubility in Water: | Dispersible |
| Specific Gravity: | 0.79kg/Litre (liquid) |
| Flashpoint: | -104°C to -60°C (propellant) |
| Flammability Limits: | LEL - 1.5% (propellant) UEL - 9.6% (propellant) |
| Auto Ignition Temperature: | Not applicable |
| Viscosity: | Not applicable |



10. STABILITY AND REACTIVITY:

Brake & Clutch Fluid – 500ml bottle

| | |
|-----------------------------------|--|
| Chemical Stability: | This product is unlikely to spontaneously decompose. |
| Conditions to Avoid: | Containers should be kept closed in order to minimise contamination. Keep from extreme heat and open flames. |
| Incompatible Materials: | Avoid water. |
| Hazardous Decomposition: Products | Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water |
| Hazardous Reactions: | In Fire Situation - Fire decomposition products from this product may form toxic mixtures in confined spaces. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. |

Brake & Parts Cleaner – 200ml aerosol can

| | |
|-----------------------------------|---|
| Chemical Stability: | Stable under normal use conditions. |
| Conditions to Avoid: | Avoid naked lights, heat or ignition sources. |
| Incompatible Materials: | Avoid storage with oxidising agents, strong acids and alkalis, organic peroxides, alkali metals, aluminium and magnesium powders. |
| Hazardous Decomposition Products: | On combustion, may emit toxic fumes of carbon monoxide (CO). Other combustion products include carbon dioxide (CO ²). |
| Hazardous Reactions: | Not determined. |

11. TOXICOLOGICAL INFORMATION:

Brake & Clutch Fluid – 500ml bottle

HUMAN HEALTH HAZARDS - ACUTE

No specific data is available for the product for chronic exposure symptoms. The ingredients are not listed as carcinogenic in Worksafe's document "Exposure Standards for Atmospheric Contaminants in the Occupational Environment" (May 1995), nor in NOHSC's "List of Designated Hazardous Substances" (April 1999).

| | |
|------------|--|
| Swallowed: | Data suggests that this product may cause gastric upset such as nausea, headache and vomiting if swallowed. However, should present no lasting problems. |
|------------|--|



11. TOXICOLOGICAL INFORMATION: continued

Brake & Clutch Fluid – 500ml bottle

- Eye: This product may be mildly irritating to eyes. However, it is unlikely to cause more than mild transient discomfort. It is also unlikely to cause any lasting effects.
- Skin: This product may be mildly irritating to skin. However, it is unlikely to cause any more than mild transient discomfort. It is also unlikely to cause any lasting effects. Prolonged and repeated skin contact may cause dermatitis due to defatting effect.
- Inhaled: Data indicates that this product may be irritating if inhaled. May lead to minor discomfort, which should quickly disappear once exposure has ceased.

Brake & Parts Cleaner – 200ml aerosol can

HUMAN HEALTH HAZARDS - ACUTE

- Swallowed: Considered an unlikely route of entry in commercial/industrial environments. The liquid is irritating to the gastro-intestinal tract. Ingestion may result in nausea, pain, vomiting. Vomit entering lungs by aspiration may cause potentially fatal chemical pneumonitis.
- Eye: The vapour is irritating to the eyes. The liquid is highly irritating and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated.
- Skin: The liquid is irritating to the skin, it is slowly absorbed and is capable of causing skin reactions, which may lead to dermatitis from repeated exposures over long periods.
- Inhaled: The vapour is highly irritating to the upper respiratory tract. Inhalation hazard is increased at higher temperatures. Inhalation exposure may cause susceptible individuals to show change in heart beat rhythm i.e., cardiac arrhythmia. Exposure must be terminated. Acute effects from inhalation of high concentrations of solvent vapour are pulmonary irritation, including coughing with nausea; central nervous system depression – characterised by headache and dizziness; and increased reaction time, fatigue and loss of co-ordination.
- If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.
- Chronic: Principal routes of exposure are by skin contact/absorption and inhalation of mist/vapour. Chronic solvent inhalation exposures may result in nervous system impairment and liver blood changes. (PATTYS) Prolonged or continuous skin contact with the liquid may cause defatting with drying, cracking, irritation and dermatitis following.

WARNING: Intentional misuse by concentrating/inhaling contents may be fatal.



12. ECOLOGICAL INFORMATION:

Brake & Clutch Fluid – 500ml bottle

Ecotoxicity: No specific data available.
Persistence and Degradability: No specific data available.
Mobility: No specific data available.
Bioaccumulation: No specific data available.

Brake & Parts Cleaner – 200ml aerosol can

Ecotoxicity: No specific data available.
Persistence and degradability: No specific data available.
Mobility: No specific data available.

13. DISPOSAL CONSIDERATIONS:

Brake & Clutch Fluid – 500ml bottle

Disposal Methods and Containers: Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible. After spills, wash area preventing runoff from entering drains.

Special Precautions for Landfill or Incineration: This material may be suitable for approved landfill. Dispose of only in accord with all regulations.

Brake & Parts Cleaner – 200ml aerosol can

Disposal Methods and Containers: Consult State Land Management Authority for disposal. Discharge contents of damaged aerosol cans at approved site. Allow small quantities to evaporate. DO NOT incinerate or puncture aerosol cans.

Special Precautions for Landfill or Incineration: Bury residues and empty aerosol cans at approved site.



14. TRANSPORT INFORMATION:

Brake & Clutch Fluid – 500ml bottle

UN Number: None Allocated
UN Proper Shipping Name:
Class and Subsidiary Risk: None Allocated
Packaging Group: None Allocated
Special Precaution for user: None Allocated
Hazchem Code: None Allocated

Brake & Parts Cleaner – 200g aerosol can

UN Number: 1950
UN Proper Shipping Name: Aerosols
Class and Subsidiary Risk: 2.1
Packaging Group: Not applicable
Hazchem Code: 2Y
Poisons Schedule: Not applicable

Classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Good by Road and Rail

Class 2.1 – Flammable Gas

Brake & Parts Cleaner shall not be loaded in the same vehicle or packed in the same freight container with :-

- Class 1 Explosives
- Class 5.1 Oxidising agents (where the miscellaneous dangerous substances are capable of igniting and burning).
- Class 5.2 Organic peroxides (where the miscellaneous dangerous substances are capable of igniting and burning).
- Class 7 Radioactive substances.

UN Number: None Allocated
UN Proper Shipping Name: None Allocated
Class and Subsidiary Risk: None Allocated
Packaging Group: None Allocated
Special Precaution for User: None Allocated
Hazchem Code: None Allocated



14. TRANSPORT INFORMATION:

Brake & Parts Cleaner – 200ml aerosol can

Land Transport (ADG):
Proper Shipping Name: Product is not regulated during transportation.

Air Transport (ICAO/IATA):
Proper Shipping Name: Product is not regulated during transportation.

Marine Transport (IMDG/IMO):
Proper Shipping Name: Product is not regulated during transportation.

15. REGULATORY INFORMATION:

Brake & Clutch Fluid – 500ml bottle

Not classified as Hazardous according to the criteria of NOHSC Australia.

Brake & Parts Cleaner – 200ml aerosol can

CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA

| | | |
|----------------|-----------------------------------|---|
| Hazard Symbol: | Xn | Harmful |
| Risk Phrase: | R11 | Highly flammable |
| | R48/20 | Harmful: danger of serious damage to health by prolonged exposure through inhalation. |
| | R36 | Irritating to eyes |
| | R66 | Repeated exposure may cause skin dryness or cracking |
| | R67 | Vapours may cause drowsiness and dizziness |
| Safety Phrase: | S2 | Keep out of the reach of children |
| | S9 | Keep container in a well ventilated place |
| | S16 | Keep away from sources of ignition – No Smoking |
| | S24/25 | avoid contact with skin and eyes |
| | S29 | Do not empty into drains |
| S51 | Use only in well-ventilated areas | |



16. OTHER INFORMATION:

Date of Issue: 30th July, 2009

MSDS Number: MSDS:186

Issue Number: E

Please Note:

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Fortron Automotive Treatments Pty Ltd's knowledge; However Fortron Automotive Treatments Pty Ltd makes no warranty whatsoever, expressed or implied, or MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, regarding the accuracy of such data or the results to be obtained from the use thereof. Fortron Automotive Treatments Pty Ltd assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.