



# Material Safety Data Sheet

---

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER:

---

Product Name: **Fortron SYNTHETIC SPRAY GREASE**

Other Names: **SYNTHETIC SPRAY GREASE - AEROSOL  
FSSG – 250 gram aerosol can**

Recommended Use: A fully synthetic lubricant enriched with lanolin and inorganic clays that provide increased corrosion resistance and waterproof properties. Synthetic Spray Grease also has non-melting and high temperature characteristics. The advanced lubrication technology provides a product that has exceptional penetrating ability and non-drying and non-staining finish. Fortron Synthetic Spray Grease will resist acids and alkalis and have no harmful effect on rubbers.

Supplier: Fortron Automotive Treatments Pty Ltd  
14-18 Sangiorgio Court, Osborne Park  
Perth, Western Australia 6017  
ACN 008 872 197 ABN 12 008 872 197  
Phone: (618) 9202 7800 (Monday – Friday 8.00am – 5.00pm)  
Fax: (618) 9202 7851  
[www.fortron.com.au](http://www.fortron.com.au)

Emergency Telephone No: 0433 088 498

---

## 2. HAZARDS IDENTIFICATION:

---

### CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA OF NOHSC

Hazard Identification:

Risk Phrase: R11 Highly flammable  
R36 Irritating to eyes

Safety Phrase: S1/2 Keep locked up and out of the reach of children  
S16 Keep away from sources of ignition – No Smoking  
S24/25 Avoid contact with skin and eyes  
S45 In case of accident or if you feel unwell seek medical advice immediately (show label where possible)

---

**3. COMPOSITION/INFORMATION ON INGREDIENTS:**

---

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Proportion % v/v</u>
Butene Co Polymer	9003-27-4	> 50%
Polyisobutene	9003-29-6	10-40%
Tetra Alkyl Ammonium Wilkenite	12001-31-9	1-10%
Smectite	1340-69-8	1-10%
Degras	8006-54-0	1-10%

---

**4. FIRST AID MEASURES:**

---

Swallowed: If swallowed **DO NOT** induce vomiting. Rinse or wash out mouth with plenty of water after which if victim is conscious, give a glass of water to drink. Seek medical attention.

For advice, contact a Poisons Information Centre. Phone Australia 13 1126; New Zealand 03 4747 000 (Not after May 2005) or 0800 764 766; or a doctor (at once).

Eye: If contact with the eye(s) occur, immediately hold the eye open and wash continuously for at least 15 minutes with fresh running water. Ensure irrigation under eyelids by occasionally lifting the upper and lower lids. If irritation persists seek medical attention. Skilled personnel should only undertake removal of contact lenses after an eye injury.

Skin: If solids or aerosol mists are deposited upon the skin wash affected areas thoroughly with water and soap if available. Seek medical attention in the event of irritation.

Inhaled: Remove the source of contamination or move the victim to fresh air. Administer artificial respiration if breathing has stopped. Keep at rest. Call for prompt medical attention.

First Aid Facilities: Safety shower, mild soap and eye wash facilities.

Advice to Doctor: Treat symptomatically.

---

## 5. FIRE FIGHTING MEASURES:

---

Extinguishing Media:	In case of fire use water spray, dry chemical or CO <sup>2</sup> .
Unusual Fire & Explosion Hazards:	Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat or flame. Heat or damage to containers may release flammable gases. Containers will explode when heated - vapour forms an explosive mixture with air. Severe explosion hazard, in the form of vapour, when exposed to flame or spark. Vapour may travel considerable distance to source of ignition. Heating may cause expansion or decomposition leading to violent rupture of containers. Containers may explode on exposure to naked flames. Rupturing containers may rocket and scatter burning materials. Hazards may not be restricted to pressure effects. May emit acrid, poisonous or corrosive fumes. On combustion, may emit toxic fumes of carbon monoxide (CO). Other combustion products include carbon dioxide. (CO <sup>2</sup> ).
Fire Fighting Precautions:	<p>Fire fighters should wear full protective clothing and self-contained breathing apparatus. If large amounts, or corrosive or toxic products are involved, wear SCBA and chemical splash suit.</p> <p>Fight fire from protected position or use unmanned hose holders or monitor nozzles. If safe to do so, move undamaged containers from fire area. Do not approach hot containers. Cool containers with water before handling. If impossible to extinguish fire, protect surroundings, withdraw from area and allow fire to burn.</p>
Hazchem Code:	2Y

---

## 6. ACCIDENTAL RELEASE MEASURES:

---

Emergency Procedures:	Methods and materials for containment and clean up:-
Procedures in case of Breakage or Leakage:	<p><b>Minor Spill:</b> Clean up spills immediately. Avoid breathing vapours and contact with skin and eyes. Wear protective clothing, impervious gloves and safety glasses. Shut off all possible sources of ignition and increase ventilation. Wipe up. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely.</p> <p><b>Major Spill:</b> Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage entering drains or watercourses. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Water spray or fog may be used to disperse/absorb vapour. Absorb or cover spill with sand, earth, inert materials or vermiculite. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Collect residues and seal in labelled drums for disposal.</p>



---

**6. ACCIDENTAL RELEASE MEASURES: - continued**

---

Other Information: Consult State Land Waste Management Authority for disposal. Discharge contents of damaged aerosol cans at approved site. Allow small quantities to evaporate. DO NOT incinerate or puncture aerosol cans. Bury residues and empty aerosol cans at approved site.

---

**7. HANDLING AND STORAGE:**

---

Precautions for Safe Handling: Store in original containers. Check that containers are clearly labelled.

Conditions for Safe Storage: Store in original containers in approved flameproof area. Do not store in pits, depressions, basements or areas where vapour may be trapped. No smoking, naked lights, heat or ignition sources.

Keep containers securely sealed. Contents under pressure.

Store away from incompatible materials. Store in a cool, dry well ventilated area. Avoid storage at temperatures higher than 40°C. Store in an upright position. Protect containers against physical damage.

Check regularly for spills and leaks.

---

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION:**

---

National Exposure Standards: None assigned for mixture. Refer to individual constituents.

Exposure Standard means the average concentration of a particular substance in the worker's breathing zone, exposure to which, according to current knowledge, should not cause adverse health effects nor cause undue discomfort to nearly all workers. It can be of three forms; time-weighted average (TWA), peak limitation, or short term exposure limit (STEL).

Time-weighted average (TWA) is defined as the concentration of that substance over an eight-hour working shift, and apply to an eight-hour day, for a five-day working week over an entire working lifetime. Short Term Exposure Limits (STEL) and Peak Limitations may also be specified for short periods of exposure such as 15 minutes.

---

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION: - continued**

---

Engineering Controls:	Provide adequate ventilation in warehouse or closed storage areas.
Personal Protective Equipment:	<p><i>Respirator Type (AS1716)</i> No special requirements. Liquid is not classified as Hazardous according to the criteria of Worksafe Australia.</p> <p><i>Skin Protection:</i> No special equipment needed when handling small quantities. Soiled work clothing should be laundered or dry-cleaned.</p> <p><i>Eye Protection:</i> No special eye protection is necessary when handling in small quantities. If eye contact is likely, then it is recommended that safety glasses or goggles be used.</p> <p><i>Hygiene Recommendations:</i> Keep an eye wash fountain available. Keep safety shower available. If clothing is contaminated, remove clothing and thoroughly wash the affected area. Launder contaminated clothing before re-use.</p>

---

**9. PHYSICAL AND CHEMICAL PROPERTIES:**

---

Appearance:	Clear grease compound.
Odour:	Bland
pH:	7
Vapour Pressure:	Not determined
Vapour Density:	Not determined
Boiling Point:	Not determined
Melting Point:	Not determined
Solubility in Water:	Nil
Specific Gravity:	0.900
Flashpoint (COC):	230°C
Flammability Limits:	LEL - Not determined UEL - Not determined
Auto Ignition Temperature:	Not applicable
Viscosity:	Not applicable

---

**10. STABILITY AND REACTIVITY:**

---

Chemical Stability:	Stable under normal use conditions.
Conditions to Avoid:	Avoid naked lights, heat or ignition sources.
Incompatible Materials:	Avoid storage with oxidising agents, strong acids and alkalis, organic peroxides, alkali metals, aluminium and magnesium powders.
Hazardous Decomposition Products:	On combustion, may emit toxic fumes of carbon monoxide (CO). Other combustion products include carbon dioxide (CO <sup>2</sup> ).
Hazardous Reactions:	Not determined.

---

**11. TOXICOLOGICAL INFORMATION:**

---

**HUMAN HEALTH HAZARDS - ACUTE**

Swallowed:	Considered an unlikely route of entry in commercial/industrial environments. If ingestion occurs the result may be nausea, pain and vomiting. Vomit entering lungs by aspiration may cause potentially fatal chemical pneumonitis.
Eye:	The vapour from the propellant is irritating to the eyes. The liquid is not highly irritating.
Skin:	The liquid is non-irritating to the skin, it is slowly absorbed and will not cause skin reactions.
Inhaled:	The vapour propellant is highly irritating to the upper respiratory tract. Inhalation hazard is increased at higher temperatures. Acute effects from inhalation of high concentrations of propellant vapour are pulmonary irritation, including coughing with nausea; central nervous system depression – characterised by headache and dizziness; and increased reaction time, fatigue and loss of co-ordination.
Chronic:	Principal routes of exposure are by skin contact and inhalation of mist/vapour. Chronic propellant inhalation exposures may result in nervous system impairment and liver blood changes. (PATTYS)

**WARNING:** **Intentional misuse by concentrating/inhaling contents may be fatal.**

---

**12. ECOLOGICAL INFORMATION:**

---

Ecotoxicity:	No information available for this product.
Persistence and Degradability:	No information available for this product.
Mobility:	No information available for this product.

---

**13. DISPOSAL CONSIDERATIONS:**

---

Disposal Methods and Containers:	Consult State Land Management Authority for disposal. Discharge contents of damaged aerosol cans at approved site. Allow small quantities to evaporate. DO NOT incinerate or puncture aerosol cans.
Special Precautions for Landfill or Incineration:	Bury residues and empty aerosol cans at approved site.



---

**14. TRANSPORT INFORMATION:**

---

UN Number: 1950  
UN Proper Shipping Name: Aerosols  
Class and Subsidiary Risk: 2.1  
Packaging Group: Not applicable  
Hazchem Code: 2Y  
Poisons Schedule: Not applicable

Classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Good by Road and Rail

Class 2.1 – Flammable Gas

Throttle Body Cleaner shall not be loaded in the same vehicle or packed in the same freight container with:-

Class 1 Explosives  
Class 5.1 Oxidising agents (where the miscellaneous dangerous substances are capable of igniting and burning).  
Class 5.2 Organic peroxides (where the miscellaneous dangerous substances are capable of igniting and burning).  
Class 7 Radioactive substances.

---

**15. REGULATORY INFORMATION:**

---

**CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA OF NOHSC**

Hazard Identification:

Risk Phrase: R11 Highly flammable  
R36 Irritating to eyes

Safety Phrase: S1/2 Keep locked up and out of the reach of children  
S16 Keep away from sources of ignition – No Smoking  
S24/25 Avoid contact with skin and eyes  
S45 In case of accident or if you feel unwell seek medical advice immediately (show label where possible)



---

**16. OTHER INFORMATION:**

---

Date of Issue: 16<sup>th</sup> March, 2009  
MSDS Number: MSDS:212  
Issue Number: B

**Please Note:**

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Fortron Automotive Treatments Pty Ltd's knowledge; However Fortron Automotive Treatments Pty Ltd makes no warranty whatsoever, expressed or implied, or MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, regarding the accuracy of such data or the results to be obtained from the use thereof. Fortron Automotive Treatments Pty Ltd assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.