



Material Safety Data Sheet

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER:

Product Name: **Fortron VACTEK SERVICE KIT WITH OCTANE BOOSTER**

Other Names: **VACTEK SERVICE KIT WITH OCTANE BOOSTER
VACKITOB – Service Kit
1 x FOB – Octane Booster – 250ml bottle
1 x VACTEK – Vactek – 325ml bottle**

Recommended Use: This service kit contains two products that will supply the following benefits:

Octane Booster – Octane Booster increases octane by as much as 3 RON. Helps stop ping, knock and hesitation. Contains premium top-end lubricants. Improves fuel economy. Helps clean jets and injectors. Reduces harmful exhaust emissions. Helps neutralise acids in aged or high sulfur fuels. Disperses moisture in fuel and fuel lines. Helps prevent formation of gums and varnish deposits. Suitable for use in leaded, unleaded and high octane petrol.

Vactek – Vactek is a concentrated formula of detergent based cleaners designed to clean combustion chambers, top rings and valves. This product also contains a powerful lubricant. Optimises petrol quality and performance.

Supplier: Fortron Automotive Treatments Pty Ltd
14-18 Sangiorgio Court, Osborne Park
Perth, Western Australia 6017
ACN 008 872 197 ABN 12 008 872 197
Phone: (618) 9202 7800 (Monday – Friday 8.30am – 5.00pm)
Fax: (618) 9202 7851
www.fortron.com.au

Emergency Telephone No: 0433 088 498



2. HAZARDS IDENTIFICATION:

CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA OF THE NATIONAL OCCUPATIONAL HEALTH AND SAFETY COMMISSION (NOHSC) AND ALSO WORKSAFE AUSTRALIA. CLASSIFIED AS DANGEROUS GOODS ACCORDING TO THE AUSTRALIAN DANGEROUS GOODS CODE.

Octane Booster – 250ml bottle

Hazard Symbol: Not applicable
Risk Phrase: Not applicable
Safety Phrase: Not applicable

Vactek – 325ml bottle

Hazard Symbol:
Risk Phrase: R10 Flammable
R38 Irritating to skin
R65 Harmful: may cause lung damage if swallowed
Safety Phrase: S2 Keep out of the reach of children
S23 Do not breathe vapour – adequate explosion-proof ventilation to control airborne concentrations
S24 Avoid contact with skin
S43 In case of fire use foam or dry powder; never use water jets
S61 Avoid release to the environment. Refer to special instructions/Safety Data Sheets

3. COMPOSITION/INFORMATION ON INGREDIENTS:

Octane Booster – 250ml bottle

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Proportion % w/w</u>
Petroleum Distillate	64742-94-5	> 10%
Petroleum Distillate	64742-95-6	> 10%
Aliphatic Hydrocarbon	64742-47-8	> 10%
Methycyclopentadienyl		
Manganese Tricarbonyl	12108-13-3	> 10%
1,3,5-trimethylbenzene	108-67-8	> 5%
1,2,4-trimethylbenzene	95-63-6	> 5%



3. COMPOSITION/INFORMATION ON INGREDIENTS: - continued

Vactek – 325ml bottle

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Proportion % w/w</u>
Kerosene (petroleum), hydrodesulfurized	64742-81-0	50-95%
Amine/Amide Carboxylate		5-20%
Solvent Neutral Paraffinic Hydrocarbon	64742-56-9	5-20%
Linoleic Acid Dimer	6144-28-1	0.1-5%
2-Pentanol 4-Methyl	108-11-2	1-10%
Toluene	108-88-3	1-20%

4. FIRST AID MEASURES:

Octane Booster – 250ml bottle

Swallowed: If swallowed and person is conscious, give milk to drink. If swallowed DO NOT induce vomiting except on advice of medical personnel. If advice cannot be obtained, take person and container to nearest emergency treatment centre. Never give anything by mouth to an unconscious person.

For advice, contact a Poisons Information Centre. Phone Australia 13 1126; New Zealand 0800 764 766; or a doctor (at once).

Eye: If contact with the eye(s) occur, immediately hold the eye open and wash continuously for at least 15 minutes with fresh running water. Seek medical attention if irritation persists.

Skin: In case of contact, remove contaminated clothing and wash before re-use. Wash skin thoroughly with water and soap.

Inhaled: If inhaled, remove to fresh air. If rapid recovery does not follow, seek medical attention.

First Aid Facilities: Safety shower, mild soap and eye wash facilities.

Advice to Doctor: Treat symptomatically.



4. FIRST AID MEASURES: - continued

Vactek – 325ml bottle

Swallowed:	If swallowed Do NOT induce vomiting. Rinse mouth with water. Give water to drink. Seek prompt medical attention. For advice, contact a Poisons Information Centre. Phone Australia 13 1126; New Zealand 03 4747 000 (Not after May 2005) or 0800 764 766; or a doctor (at once).
Eye:	If contact with the eye(s) occurs, immediately hold the eye open and wash continuously for at least 15 minutes with fresh running water. Ensure irrigation under eyelids by occasionally lifting the upper and lower lids. Seek medical advice.
Skin:	Remove contaminated clothing and wash skin with plenty of water for at least 15 minutes. Contaminated clothing is to be laundered before re-use. Dispose of work boots that are contaminated internally.
Inhaled:	Remove the source of contamination or move the victim to fresh air, avoid becoming a casualty. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing has stopped apply artificial respiration immediately. Seek medical advice.
First Aid Facilities:	Safety shower, mild soap and eye wash facilities.
Advice to Doctor:	Treat symptomatically. Because of risk of aspiration, gastric lavage should only be undertaken after endotracheal intubation. Note the nature of this product.

5. FIRE FIGHTING MEASURES:

Octane Booster – 250ml bottle

Extinguishing Media:	Use foam, dry chemical, carbon dioxide, vaporising liquid or water delivered as a fine spray.
Unusual Fire & Explosion Hazards:	Combustible liquid, C2.
Fire Fighting Precautions:	Self contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.
Hazchem Code:	None Allocated



5. FIRE FIGHTING MEASURES: - continued

Vactek – 325ml bottle

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam, and water fog. Foam is the preferred medium for large fires. Unsuitable extinguishing media – Do not use water in a jet.

Unusual Fire & Explosion Hazards: Light hydrocarbon vapours can build up in the headspace of tanks. These can cause flammability/explosion hazards, even at temperatures below the normal flash point. Tank headspaces should always be regarded, as potentially flammable and care should be taken to avoid static electricity discharge and all ignition sources during filling, ullaging and sampling from storage tanks. Hoses should be electrically continuous. Ensure equipment used is properly earthed or bonded to the tank structure. Will present a flammability hazard if heated above the flash point but bulk liquids at normal storage temperatures present a low fire hazard. If fuel contacts hot surfaces, or leaks from high pressure fuel pipes, the vapour and/or mists generated will create a flammability or explosion hazard. Empty containers represent a fire hazard as they may contain remaining flammable residues and vapour. Do not weld, heat or drill the container. Do not introduce an ignition source. Heating may cause an explosion. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids.

Fire Fighting Precautions: If a significant quantity of this product is involved in a fire, call the fire brigade. Immediately evacuate the area of unnecessary personnel. When fighting fires involving significant quantities of this product, wear safety boots, non-flammable overalls, gloves, hat goggles and self contained breathing apparatus. All skin areas should be covered. Ensure that no spillage enters drains or water courses.

Hazchem Code: 3[Y]

6. ACCIDENTAL RELEASE MEASURES:

Octane Booster – 250ml bottle

Emergency Procedures: Eliminate all sources of ignition in the vicinity of the spill or released vapour. Stop the source of the leak or release. Clean up releases as soon as possible. Observing precautions in personal protection equipment. Contain liquid to prevent further contamination of soil, surface water or ground water.

Methods and Materials for Containment and Clean Up:- Small Spills: Avoid breathing vapours and contact with skin and eyes. Wear protective clothing, impervious gloves and safety glasses. Shut off all possible sources of ignition (flames, hot surfaces and electrical, static or frictional sparks). Increase ventilation. Absorb with inert material and dispose of in accordance with local, state and federal regulations. Incinerate only in approved facility. Do not incinerate closed containers.





6. ACCIDENTAL RELEASE MEASURES: - continued

Octane Booster – 250ml bottle

Large Spills: Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage entering drains or watercourses. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Water spray or fog may be used to disperse/absorb vapour. Absorb or cover spill with sand, earth, inert materials or vermiculite. Collect residues and seal in labelled drums for disposal.

Disposal: Follow state or local authority regulations and guidelines for disposal of the waste. Do not allow to enter drains, sewers or water courses – inform the local authorities if this occurs.

Vactek – 325ml bottle

Emergency Procedures:

In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. Wear full protective chemically resistant clothing including facemask, face shield, gauntlets and self-contained breathing apparatus. Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. Avoid using sawdust or other combustible material. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage.

Methods and Materials for Containment and Clean Up:-

Small Spills:/Major Spills - Absorb onto sand, vermiculite or other suitable absorbent material. Avoid using sawdust or other combustible material. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage.

7. HANDLING AND STORAGE:

Octane Booster - 250ml bottle

Combustible Liquid, C2.

Precautions for Safe Handling: Avoid skin and eye contact.

Conditions for Safe Storage: Store and dispense only in well ventilated areas away from heat and sources of ignition. Keep apart from oxidising substances.

Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.



7. HANDLING AND STORAGE: - continued

Vactek – 325ml bottle

Precautions for Safe Handling: Keep out of reach of children. Do not breathe vapour. Avoid contact with skin. In case of fire use foam or dry powder; never use water jets. Avoid release to the environment.

Always wash hands before smoking, eating or using the toilet. Wash contaminated clothing and other protective equipment before storing and re-using.

Conditions for Safe Storage: This product is classed as UN1268, Dangerous Goods Class 3 Flammable Liquids.

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with:-

- Class 1 Explosives
- Class 2.1 Flammable Gases where flammable liquids and flammable gases are both in bulk
- Class 2.3 Toxic Gases
- Class 4.2 Spontaneously Combustible Substances
- Class 5.1 Oxidising Agents
- Class 5.2 Organic Peroxides
- Class 6 Toxic Substances, except Flammable Liquid is nitro methane
- Class 7 Radioactive Substances

They may however be loaded in the same vehicle or packed in the same freight container with Class 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk). Class 2.2 (Non Flammable Non Toxic Gases) Class 4.3 (Dangerous When Wet Substances) Toxic 6 (Toxic Substances, except where Flammable Liquid is nitro methane) Class 8 (Corrosive Substances) Class 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

This product is a S5 Poison. Observe all relevant regulations regarding sale, transport and storage of this class of product. Containers should be kept closed in order to minimise contamination. Keep from extreme heat and open flames, and make sure that the product does not come into contact with substances listed under “Materials to avoid” below.



8. EXPOSURE CONTROLS/PERSONAL PROTECTION:

Octane Booster – 250ml bottle

National Exposure Standards:

The following exposure standards have been issued by OSHA/ACGIH

	TWA		STEL	
	ppm	mg/m ³	ppm	mg/m ³
Liquid hydrocarbons		5		10

Exposure Standard means the average concentration of a particular substance in the worker's breathing zone, exposure to which, according to current knowledge, should not cause adverse health effects nor cause undue discomfort to nearly all workers. It can be of three forms; time-weighted average (TWA), peak limitation, or short term exposure limit (STEL).

Time-weighted average (TWA) is defined as the concentration of that substance over an eight-hour working shift, and apply to an eight-hour day, for a five-day working week over an entire working lifetime. Short Term Exposure Limits (STEL) and Peak Limitations may also be specified for short periods of exposure such as 15 minutes.

Engineering Controls:

Use local exhaust ventilation to control mists or vapours. Additional ventilation may be required to maintain air concentrations below recommended limits.

Personal Protective Equipment: Avoid contact with the skin and eyes, and avoid breathing vapours or mists.

Respirator Type (AS 1716)

Airborne concentrations should be kept to lowest levels possible. If vapours, mists or fumes are generated and the occupational exposure limit of the product, or any component of the product, is exceeded, use appropriate AS/NZS 1715/1716 approved air purifying or air supplied respirator after determining the airborne concentration of the contaminant. Air supplied respirators should always be worn when airborne concentration of the contaminant or oxygen content is unknown.

Skin Protection

If skin contact is likely, wear impervious protective clothing and/or gloves. Soiled work clothing should be laundered or dry-cleaned.

Eye Protection

If eye contact is likely, then it is recommended that safety glassed or goggles be used.

A time weighted average (TWA) concentration for an 8 hour day, and 5 day week has not been established by NOHSC Australia for any of the major ingredients in this product. There is a blanket limit of 10mg/m³ for dusts or mists when limits have not otherwise been established.





8. EXPOSURE CONTROLS/PERSONAL PROTECTION: - continued

Vactek – 325ml bottle

National Exposure Standards: Worksafe Australia has assigned the following standards for this product.

SUBSTANCE	Occupational Exposure Limits	TWA	TWA
		ppm	mg/m3
Kerosene (petroleum) Hydrodesulfurized			10
Toluene		50	188

Exposure Standard means the average concentration of a particular substance in the worker’s breathing zone, exposure to which, according to current knowledge, should not cause adverse health effects nor cause undue discomfort to nearly all workers. It can be of three forms; time-weighted average (TWA), peak limitation, or short term exposure limit (STEL).

Time-weighted average (TWA) is defined as the concentration of that substance over an eight-hour working shift, and apply to an eight-hour day, for a five-day working week over an entire working lifetime. Short Term Exposure Limits (STEL) and Peak Limitations may also be specified for short periods of exposure such as 15 minutes.

Engineering Controls:

In industrial situation, concentration values below the TWA value should be maintained. Values may be reduces by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high; you are advised to modify the process or environment to reduce the problem.

Personal Protective Equipment:

Respiratory Protection: It is usually safe to not use a dust mask or respirator protection on account of this product. However, if the product is being used in dusty or confined conditions, use of a mask or respirator may be preferred. For help in selecting suitable equipment, consult AS/NZS1715.

Protective Gloves: Impermeable protective gloves should be worn when you are using this product. Failure to do so will lead to irritation of the skin. For help in selecting suitable equipment, consult AS2161.

Eye Protection: Protective eyewear is not normally necessary when using this product. However, it is always prudent to use protective eyewear. Consult AS1336 and AS/NZS1337 for advice on Industrial Eye Protection.

Clothing Protection: Clean impermeable overalls or protective clothing should always be worn when handling this product, clothing should be destroyed. Consult AS2919 for advice on Industrial Clothing.

Safety Boots: Wearing safety boots in industrial situations is advisory. Consult AS/NZS for advice on Occupational Protective Footwear.

Hygiene Recommendations: Always wash hands before smoking, eating or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.





9. PHYSICAL AND CHEMICAL PROPERTIES:

Octane Booster – 250ml bottle

Appearance:	Liquid amber in colour
Odour:	Slightly oily odour
pH:	Not applicable
Vapour Pressure:	Not applicable
Vapour Density:	Not available
Boiling Point:	Not applicable
Melting Point:	Not available
Solubility in Water:	Nil
Specific Gravity:	0.83
Flashpoint:	72° (Closed Cup) Pensky - Martens
Flammability Limits:	LEL Not applicable UEL Not applicable
Volatiles:	> 90%

Vactek – 325ml bottle

Appearance:	Red liquid, lighter than water
Odour:	Spirit odour
pH:	Not applicable
Vapour Pressure:	0.2 kPa @ 20°C
Vapour Density:	> 1 (Heavier than air)
Boiling Point:	150°C - 280°C @ 100kPa
Melting Point:	< -20°C
Solubility in Water:	Insoluble
Specific Gravity:	0.80 g/cm ³
Flashpoint:	> 29°C (Closed Cup) Pensky - Martens
Flammability Limits:	LEL 0.7 % UEL 5.0 %
Auto Ignition Temperature:	> 200°C
Volatile Component:	Slowly volatile at 100%, but completely volatile at high temperatures
Evaporation Rate:	0.14 (n-butyl acetate = 1)

10. STABILITY AND REACTIVITY:

Octane Booster – 250ml bottle

Chemical Stability:	Stable under normal conditions of storage and handling.
Conditions to Avoid:	Combustible substance. Remove all sources of ignition, heat and naked flames.
Incompatible Materials:	Avoid oxidizing agents.
Hazardous Decomposition Products:	None applicable.
Hazardous Reactions:	None applicable.



10. STABILITY AND REACTIVITY: - continued

Vactek – 325ml bottle

Chemical Stability:	This product is unlikely to spontaneously decompose.
Conditions to Avoid:	Avoid heat, sparks, open flames and other ignition sources.
Incompatible Materials:	Strong oxidising agents.
Hazardous Decomposition Products:	Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water.

11. TOXICOLOGICAL INFORMATION:

Octane Booster – 250ml bottle

HUMAN HEALTH HAZARDS - ACUTE

Swallowed:	Considered an unlikely route of entry in commercial and industrial environments. Ingestion of this material may be harmful (if swallowed and causes vomiting, pain and nausea). Aspiration during ingestion or vomiting can result in severe pulmonary damage.
Eye:	May cause slight irritation, discomfort, redness and temporary impaired vision to the eyes.
Skin:	The liquid is irritating to the skin and is capable of causing skin reactions, which may lead to dermatitis from repeated exposures over long periods.
Inhaled:	The vapour/mist is discomforting and is characterised by headaches, nausea and dizziness. Prolonged inhalation will cause fatigue and loss of co-ordination.
Chronic:	Prolonged or repeated skin contact may cause dermatitis.

Vactek - 325ml bottle

HUMAN HEALTH HAZARDS - ACUTE

Swallowed:	Because of the low viscosity of this product, it may directly enter the lungs if swallowed, or if subsequently vomited. Once in the lungs, it is very difficult to remove and can cause severe injury or death.
Eye:	May cause eye irritation but will not damage eye tissue.
Skin:	May cause skin irritation after prolonged or repeated contact, It is likely to cause discomfort and effects such as moderate to severe itchiness, blistering and skin reddening.
Inhaled:	High vapour concentrations may cause irritation to mucous membranes and the respiratory tract. Prolonged exposure to vapours can affect the central nervous system and result in headaches and dizziness or unconsciousness.



11. TOXICOLOGICAL INFORMATION: - continued

Vactek - 325ml bottle

Chronic: No specific data is available for this product for chronic exposure symptoms. The ingredients are not listed as carcinogenic in Worksafe's document "Exposure Standards for Atmospheric Contaminants in the Occupational Environment" (May 1995), nor in NOHSC's "List of Designated Hazardous Substances" (April 1999).

12. ECOLOGICAL INFORMATION:

Octane Booster – 250ml bottle

Avoid contaminating waterways.

Ecotoxicity: No information is available on this product.

Persistence and Degradability: No information is available on this product.

Mobility: No information is available on this product.

Vactek – 325ml bottle

Environmental Hazards: No specific data available.

Ecotoxicity: No specific data available.

Persistence and Degradability: No specific data available.

Mobility: No specific data available.

13. DISPOSAL CONSIDERATIONS:

Octane Booster – 250ml bottle

Disposal Methods and Containers: Disposal: Follow state or local authority regulations and guidelines for disposal of the waste. Do not allow to enter drains, sewers or water courses – inform the local authorities if this occurs.

Special Precautions for Landfill or Incineration: No special precautions required for product.



13. DISPOSAL CONSIDERATIONS: - continued

Vactek – 325ml bottles

Disposal Methods
and Containers:

Absorb onto sand, vermiculite or other suitable absorbent material. Avoid using sawdust or other combustible material. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage. Recycle containers wherever possible. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Dispose of only in accord with all regulations.

Special Precautions for
Landfill or Incineration:

Dispose of via an authorised person/licensed waste disposal contractor in accordance with local regulations. Incineration may be carried out under controlled conditions provided that local regulations for emissions are met. Empty containers may contain some residual product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

14. TRANSPORT INFORMATION:

Octane Booster – 250ml bottle

UN Number: None Allocated
UN Proper Shipping Name: None Allocated
Class and Subsidiary Risk: None Allocated
Packaging Group: None Allocated
Special Precaution for User: None Allocated
Hazchem Code: None Allocated

Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road or Rail.

Land Transport (ADG):
Proper Shipping Name: Product is not regulated during transportation.

Air Transport (ICAO/IATA):
Proper Shipping Name: Product is not regulated during transportation.

Marine Transport (IMDG/IMO):
Proper Shipping Name: Product is not regulated during transportation.





14. TRANSPORT INFORMATION: - continued

Vactek – 325ml bottle

UN Number: 1268
UN Proper Shipping Name: Petroleum Products N.O.S
Class and Subsidiary Risk: 3
Packaging Group: III
Special Precaution for User: None Allocated
Hazchem Code: 3[Y]

Land Transport (ADG):

UN Number: 1268
UN Proper Shipping Name: Petroleum Products N.O.S
Class and Subsidiary Risk: 3
Packaging Group: III
Special Precaution for User: None Allocated
Hazchem Code: 3[Y]

Air Transport (ICAO/IATA):

UN Number: 1268
UN Proper Shipping Name: Petroleum Products N.O.S
Class and Subsidiary Risk: 3
Packaging Group: III
Special Precaution for User: None Allocated
Hazchem Code: 3[Y]

Marine Transport (IMDG/IMO):

UN Number: 1268
UN Proper Shipping Name: Petroleum Products N.O.S
Class and Subsidiary Risk: 3
Packaging Group: III
Special Precaution for User: None Allocated
Hazchem Code: 3[Y]

15. REGULATORY INFORMATION:

Octane Booster – 250ml bottle

Statement of Hazardous Nature: Not classified as Hazardous according to the criteria of National Occupational Health and Safety Commission (NOHSC)
Hazard Symbol: Not applicable
Risk Phrase: Not applicable
Safety Phrase: Not applicable



15. REGULATORY INFORMATION:

Vactek – 325ml bottle

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Poison Schedule: S5

EC Symbols:

EC Risk Phrase: R10 Flammable
R38 Irritating to skin
R65 Harmful: may cause lung damage if swallowed.

EC Safety Phrase: S2 Keep out of the reach of children.
S23 Do not breathe vapour – adequate explosion-proof ventilation to control airborne concentrations
S24 Avoid contact with skin
S43 In case of fire use foam or dry powder; never use water jets
S61 Avoid release to the environment. Refer to special instructions/Safety Data Sheets

16. OTHER INFORMATION:

Date of Issue: 18th July 2011

MSDS Number: MSDS:179

Issue Number: G

Please Note:

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Fortron Automotive Treatments Pty Ltd's knowledge; However Fortron Automotive Treatments Pty Ltd makes no warranty whatsoever, expressed or implied, or MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, regarding the accuracy of such data or the results to be obtained from the use thereof. Fortron Automotive Treatments Pty Ltd assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.