



PRODUCT SAFETY DATA SHEET

1. Identification of the substance/preparation and of the company/undertaking

Product details

Trade name: **AIR CONDITIONING TREATMENT** **W 160**

Article number: 18-00000-1016

Application of the substance / the preparation Interior vehicle cleaner

Supplier: Fortron Marketing & Distribution, Farringdon Road, Cumnor, Oxford OX2 9RE

Emergency information: Emergency Phone Number : 07976540170 or 079767339153

2. Hazards identification

Hazard description: F+ Extremely flammable

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

R 12 Extremely flammable. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Buildup of explosive mixtures possible without sufficient ventilation.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

GHS label elements

Flame Danger

H222 - Extremely flammable aerosol.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

Storage:

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

3. Composition/information on ingredients**Chemical characterization**

Description: Active substance with propellant

Dangerous components:

64-17-5 ethanol F; R 11 Danger: flame 2.6/2 EINECS: 200-578-6	25-<50 %
106-97-8 butane (containing < 0.1% butadiene (203-450-8)) F+; R 12 Danger: flame 2.2/1 Warning: gas cylinder 2.5/C EINECS: 203-448-7	25-<50 %
74-98-6 propane F+; R 12 Danger: flame 2.2/1 Warning: gas cylinder 2.5/C EINECS: 200-827-9	10-<25 %
67-63-0 propan-2-ol Xi, F; R 11-36-67 Danger: flame 2.6/2 Warning: exclamation mark 3.3/2, 3.8/3 EINECS: 200-661-7	1.0-<2.5 %

Ingredients according to detergents guideline 648/2004/EC

aliphatic hydrocarbons >= 30%
disinfectants < 5%

4. First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Do not induce vomiting; call for medical help immediately.

5. Fire-fighting measures

Suitable extinguishing agents: Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam

For safety reasons unsuitable extinguishing agents: Water with full jet

Protective equipment: Mount respiratory protective device.

6. Accidental release measures

Person-related safety precautions:

Wear protective equipment. Keep unprotected persons away.

Measures for environmental protection:

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

Measures for cleaning/collecting: Ensure adequate ventilation.

7. Handling and storage

Handling:

Information for safe handling:

Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.

Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurized containers.

Further information about storage conditions:

Keep receptacle tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

8. Exposure controls/personal protection

Additional information about design of technical facilities:

No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

64-17-5 ethanol

WEL: Long-term value: 1920 mg/m³, 1000 ppm

106-97-8 butane (containing < 0.1% butadiene (203-450-8))

WEL: Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

74-98-6 propane

WEL: Short-term value: 3600 mg/m³, 2000 ppm

Long-term value: 1800 mg/m³, 1000 ppm

67-63-0 propan-2-ol

WEL: Short-term value: 1250 mg/m³, 500 ppm

Long-term value: 999 mg/m³, 400 ppm

Additional information:

The lists valid during the making were used as basis.

Personal protective equipment:

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter AX/P2

Protection of hands: Solvent resistant gloves.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves Nitrile rubber, NBR

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles

Body protection: Use protective suit.

9. Physical and chemical properties

General Information

Form: Aerosol

Colour: According to product specification

Odour: Characteristic

Value/Range Unit Method

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: -44 °C

Flash point: -97 °C

Ignition temperature: 365 °C

Self-igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower: 1.5 Vol %

Upper: 15.0 Vol %

Vapour pressure: at 20 °C 4 bar

Density: at 20 °C 0.65 g/cm³

Solubility in / Miscibility with

water: Not miscible or difficult to mix.

Solvent content:

Organic solvents: 99.8 %

10. Stability and reactivity

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Materials to be avoided:

Dangerous reactions: No dangerous reactions known.

Dangerous decomposition products: No dangerous decomposition products known.

11. Toxicological information

Acute toxicity:

LD/LC50 values relevant for classification:

67-63-0 propan-2-ol

Oral: LD50: 4570 mg/kg (rat)

Dermal: LD50: 13400 mg/kg (rabbit)

Inhalative: LC50/4 h: 30 mg/l (rat)

Primary irritant effect:

On the skin: No irritant effect.

On the eye: No irritating effect.

Sensitization: No sensitizing effects known.

12. Ecological information

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13. Disposal considerations

Product:

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

14. Transport information

Land transport ADR/RID (cross-border)

ADR/RID class: 2 5F Gases.

Danger code (Kemler): -

UN-Number: 1950

Packaging group: -

Hazard label 2.1

Description of goods: 1950 AEROSOLS

Limited quantities (LQ) LQ2

Transport category 2

Tunnel restriction code D

Maritime transport IMDG:

IMDG Class: 2.1

UN Number: 1950

Label 2.1

Packaging group: -

EMS Number: F-D,S-U

Marine pollutant: No

Proper shipping name: AEROSOLS

Air transport ICAO-TI and IATA-DGR:

ICAO/IATA Class: 2.1

UN/ID Number: 1950

Label 2.1

Packaging group: -

Proper shipping name: AEROSOLS, flammable

UN "Model Regulation": UN1950, AEROSOLS, 2.1

15. Regulatory information

Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product: F+ Extremely flammable

Risk phrases: 12 Extremely flammable.

Safety phrases:

2 Keep out of the reach of children.

16 Keep away from sources of ignition — No smoking.

29 Do not empty into drains.

46 If swallowed, seek medical advice immediately and show this container or label.

51 Use only in well-ventilated areas.

Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Buildup of explosive mixtures possible without sufficient ventilation.

National regulations:

Technical instructions (air):

Class Share in %

NK 50-100

VOC-CH 99.75 %

VOC-EU 648.4 g/l

Danish MAL Code 2-1

16. Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant R-phrases

11 Highly flammable.

12 Extremely flammable.

36 Irritating to eyes.

67 Vapours may cause drowsiness and dizziness.

Department issuing MSDS: Health & Safety Department

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

MAL-Code: Måleteknisk Arbejdshygienisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

- *** Data compared to the previous version altered. ***